



Young softshell jacket with fashionable details

3-layer functional material with TPU-membrane

Wind- and waterproof (5,000 mm water column), breathable and

permeable to vapour

Non-taped seams

Stand-up collar, detachable hood

2 side pockets and 1 zipped breast pocket

Elastic cord with stopper on hood and waistband

Zip for decoration

Zips and lateral band in contrasting colour

Knitted sleeve cuffs JN1077: lightly waisted

Fabric: Outer fabric (290 g/m²): 100%

polyester

Country of origin: Volksrepublik China

Care instructions:



Partner article:



Ladies' Maritime Jacket Art-Nr.: JN1077

Available colours

	s	M	L	XL	XXL	3XL
Weight in g	749 g	762 g	770 g	788 g	798 g	211 g
VPE	1/20	1/20	1/20	1/20	1/20	1/20
(Pcs. per inner packaging						
/ pcs. per outer packaging						

Measurements in cm	S	M	L	XL	XXL	3XL
1/2 chest	53,00 cm	56,00 cm	60,00 cm	64,00 cm	68,00 cm	72,00 cm
1/2 bottom width	50,00 cm	53,00 cm	57,00 cm	61,00 cm	65,00 cm	69,00 cm
front length from shoulder	69,00 cm	71,00 cm	73,00 cm	75,00 cm	77,00 cm	79,00 cm
length back from shoulder	72,00 cm	74,00 cm	76,00 cm	78,00 cm	80,00 cm	82,00 cm
sleeve length	68,00 cm	70,00 cm	71,00 cm	73,00 cm	74,00 cm	74,00 cm

Available colours





sun-yellow/navy/white (116C, 296C, whiteC)



OEKO-TEX® Standard 100

OEKO-Tex® CONFIDENCE IN TEXTILES STANDARD 100 15.0.70467 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100



Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



Breathable-Permeable to water vapour

Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m2 within 24 hours. The higher this figure, the more breathable the textile is.



Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.

Stand: 03.07.2025 - 08:39:42