


Classic softshell jacket in sporty design made of recycled polyester

Pleasantly soft 3-layer function material with TPU-membrane
 Wind and water repellent (5,000 mm water column), breathable and permeable to water vapour (3.000 g/m²/24h)
 Non-taped seams
 Inside made of micro fleece, mesh lining in the front
 Stand-up collar
 2 side pockets and 1 breast pocket with zips
 Full-length under-panel 2-way zip with chin cup
 Elastic cord on hem for width-adjustment
 Zips: YKK
 JN1171: lightly waisted

Fabric: Outer fabric (290 g/m²): 100% polyester (recycled)
 Lining: 100% polyester

Country of origin: Bangladesch

Care instructions:

Partner article:


Men's Softshell Jacket
 Art-Nr.: JN1172

Available colours

	XS	S	M	L	XL	XXL
Weight in g	535 g	550 g	585 g	620 g	655 g	695 g
VPE (Pcs. per inner packaging / pcs. per outer packaging)	1/20	1/20	1/20	1/20	1/20	1/20

Measurements in cm	XS	S	M	L	XL	XXL
1/2 chest	48,00 cm	50,00 cm	52,00 cm	56,00 cm	60,00 cm	64,00 cm
1/2 bottom width	50,00 cm	52,00 cm	54,00 cm	58,00 cm	62,00 cm	66,00 cm
front length from shoulder	61,00 cm	62,00 cm	64,00 cm	66,00 cm	68,00 cm	70,00 cm
length back from shoulder	63,00 cm	64,00 cm	66,00 cm	68,00 cm	70,00 cm	72,00 cm
sleeve length	60,00 cm	61,00 cm	62,00 cm	63,00 cm	63,00 cm	63,00 cm

Available colours

 black (blackC)
 nautic-blue (293U)

 brown (476C)
 navy (296C)

 graphite (432C)
 red (200C)




OEKO-TEX® Standard 100

OEKO-Tex® CONFIDENCE IN TEXTILES STANDARD 100 15.0.70467 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100



Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



Recycled Polyester

PET bottles are recycled to create a new fashion. Plastic bottles are crushed, melted down and spun to yarn again, which is sometimes completely integrated into the production.



Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.